

## **SPECIFICATIONS**

**QUALITY WINDOW TINT** 

## INSPIRE SERIES

Inspire Series is the most affordable tint with modern technology in ensuring a comfortable drive. Is an improved dyed tint that delivers UV protection and a look that's made to last a lifetime.

## Technical Specification (as measured on 3mm glass)

	% Visible Light Transmission (VLT)	% Visible Light Reflectance (Glass Side)	% Total Solar Energy Rejection (TSER)	% IR Energy Rejection (IRER)*	% Selective IR Rejection (SIRR)**	% UV Rejection (UVR)
INSPIRE 70	64	7	50	65	45	99
INSPIRE 50	51	6	38	65	34	99
INSPIRE 35	37	6	42	65	44	99
INSPIRE 15	18	6	58	65	40	99
INSPIRE 5	8	6	70	65	73	99
INSPIRE 3	4	6	72	65	78	99

<sup>\*</sup> All performance data captured and calculated using a Spectrophotometer with films applied to 1/8" (3mm) clear glass. Visible light and solar energy data are reported using EN 410 methodology & IR rejection data are reported at peak wavelength, 1000nm. Product performance tolerances for visible light, solar energy, UV rejection and IR rejection values are +/-3%. Actual performance will vary based on several factors, including glass type and properties.

\*\*SIRR is a measurement of solar infrared radiation (900-1000nm) not directly transmitted through glass.

Warranty Coverage
Comprehensive 3-Year
Limited Warranty

PIONEER IN GRAPHENE GRX® TECHNOLOGY



For more information, visit us at: www.vertekfilms.com



<sup>\*</sup>IRER is a more complete measurement of heat experienced from solar infrared radiation (900-1000nm) including absorberd and re-radiated energy.